



Northland JCB is proud to serve New England with a core commitment to putting our customers first and matching the right equipment for the right applications. Northland JCB thrives on a reputation built by fanatical customer service and an unparalleled service model. We make doing business with us simple and easy. It is our commitment to customer service that has enabled us to develop enduring customer relationships.

We are honored to partner with JCB to offer a wide selection of new and used construction equipment including backhoes loaders, excavators, compact track loaders & skid steers, telehandlers, wheel loaders and more to fulfill our customers' needs.

We are a one-stop equipment dealer offering new and used construction equipment sales, rental, parts, and service with six locations serving Massachusetts, New Hampshire, Maine, Connecticut, and Rhode Island.

Standard Equipment

Standard Equipment and Features & Benefits related to this product are subject to change without notice

ENGINE	4.4L (268CID) 74 SAE Gross hp, JCB Ecomax T4F diesel engine with no DPF, centrifugal dry type dual stage air cleaner. Fuel filter with water separator, 1000 CCA battery; variable speed hydraulically driven fan which can either manually or automatically reverse to clean out debris around the radiator and oil cooler.
TRANSMISSION	EH (Electo-Hydraulic) Controls with hydrostatic transmission. Standard two (2) speed transmission provides a low range of 0 - 4.8 mph and a high range of 0 - 7.8 mph in both forward and reverse. Standard Creep speed provides operation from 0 to 1/2 of full speed for special applications.
RUBBER TRACKS	Fitted with 17.7" wide tracks provide a machine width of 78" and a ground bearing pressure of 5.0 psi.
BRAKES	Machine braking provided through the hydrostatic transmission. Parking brake consists of multiple disc, oil immersed, spring applied hydraulic release that provides a fail safe with the engine off. Electrically activated through a switch on the instrument panel or by raising seat bar.
ELECTRICAL	Meets IP69 (external) IP67 (internal) water ingress standard. Worklights, 2 Front and 1 Rear, Reverse Alarm, Horn, and 12V Accessory Socket.
INSTRUMENTS	Audible and visual warning systems, right and left side mounted instrument panels. Standard electronic throttle control with foot throttle.
CAB	SAE certified ROPS/FOPS, left side entry. Units are equipped with a suspension seat with adjustable arm pods, an operator restraint interlock for safety. Right Hand glass standard on all units.
HYDRAULICS	24gpm @ 3335psi standard flow and 33gpm @ 3335psi Highflow auxiliary hydraulics
LOADER	Rated Operating Capacity of 3600 lbs, Radial Lift Loader Design provides a radial lift path, and with a two stage telescopic boom, a hinge pin height of 159" (13'-3") and 96" (8') of forward reach. Auxiliary hydraulic circuit and high flow are standard for operation of hydraulic powered attachments. All machines are equipped with: Automatic Attachment Leveling System, Smooth Ride System,

